

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE WEST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 4, 5, 10, 11, 14, AND 15,

IN

TOWNSHIP 20 SOUTH, RANGE 7 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Daniel T. Gillins
Cadastral Surveyor

Under the Supervision of

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under Special Instructions dated and approved **August 31, 2007**, which provided for the surveys included under Group Number **1056**, with Assignment Instructions dated **October 5, 2007**, and Reassignment Instructions dated **January 14, 2008**.

Survey commenced **September 3, 2007**
Survey completed **April 12, 2008**

INDEX DIAGRAM

Township 20 South, Range 7 West

8 5 6	7 34 5	6 24 4	6 18 3	6 14 2	9 1
33 5 7	33 32 8	24 23 9	18 17 10	13 12 11	8 12
31 4 18	31 30 17	23 22 16	16 15 15	10 9 14	10 13
29 4 19	29 28 20	21 21 21	15 15 22	11 23	24
28 3 30	28 27 29	20 20 28	14 27	26	25
26 3 31	26 25 32	19 18 33	34	35	36

The Subdivision of Section 4.....Page 34
The Subdivision of Section 5.....Page 36
The Subdivision of Section 10.....Page 38
The Subdivision of Section 11.....Page 39
The Subdivision of Section 14.....Page 40
The Subdivision of Section 15.....Page 41

[illegible]

SOUTH BOUNDARY (Fourth Standard Parallel South)

All	J. Bausman	1869		
Portion			A. Nelson, et al.	1934-36
All			R. Gentry, et al.	1937

EAST BOUNDARY

All A. Nelson, et al. 1934

WEST BOUNDARY

All	J. Bausman	1871	
All		A. Nelson	1940

NORTH BOUNDARY

All	J. Bausman	1871		
Portion			A. Nelson, et al.	1934-36
Portion			A. Nelson & E. Bird	1941

SUBDIVISION

Portion	J. Bausman	1871		
Portion	A. Nelson, et al.	1934-36	A. Nelson, et al.	1934-36

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1056, dated August 31, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DELTAMUNI_UT2004 CORS ARP, MARYSVALE_UT2006 CORS ARP, and CARBON COUNTY COU CORS ARP.

The geographic position of the corner of sections 1, 2, 35, and 36, on the north boundary of Township 20 South, Range 7 West, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 39°06'42.569" N. Longitude: 112°35'50.048" W. N.A.D. 1983,
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of the West Boundary,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Bausman in 1871 and the
Resurvey Executed by A. Nelson in 1940

Beginning at the standard corner of Township 20 South, Ranges 7 and 8 West, monumented with an iron post, 3 inches in diameter, firmly set, projecting 3 inches above ground, at a fence corner with barbed wire fences extending E-NE and SW, with brass cap marked as described in the official record of the 1937 resurvey.

N. 0°25.1' E., between sections 31 and 36.

- 40.416 The 1/4 section corner of sections 31 and 36, monumented with an iron post, 1 inch in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 2 ft. base, 1 ft. high, west of corner.

Set a steel fence post alongside the iron post.

N. 0°25.0' E., beginning new measurement.

- 40.391 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 2 inches in diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 3 ft. base, 1 ft. high, west of corner.

Set a steel fence post alongside the iron post.

N. 0°35.5' E., between sections 25 and 30.

- 40.300 The 1/4 section corner of sections 25 and 30, monumented with an iron post, 1 inch in diameter, firmly set, projecting 8 inches above the ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1940 resurvey.

Set a steel fence post alongside the iron post.

N. 0°24.7' E., beginning new measurement.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.309** The corner of sections 19, 24, 25, and 30, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 3 ft. base, 1 ft. high, 2 links west of corner.

Set a steel fence post alongside the iron post.

N. 0°30.7' E., between sections 19 and 24.

- 40.394** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 1 inch in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 2 ft. base, 1 1/2 ft. high, 2 links west of corner.

Set a steel fence post alongside the iron post.

N. 0°30.2' E., beginning new measurement.

- 40.389** The corner of sections 13, 18, 19, and 24, monumented with an iron post, 2 inches in diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 2 ft. base, 1 1/2 ft. high, 2 links west of corner.

Set a steel fence post alongside the iron post.

N. 0°28.5' E., between sections 13 and 18.

- 40.426** The 1/4 section corner of sections 13 and 18, monumented with an iron post, 1 inch in diameter, firmly set, projecting 13 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a lava stone, firmly set along the west side of corner.

Set a steel fence post along the east side of the iron post.

N. 0°28.7' E., beginning new measurement.

- 40.425** The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 inches in diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a mound of stone, 2 ft. base, 6 inches high, west of corner.

Set a steel fence post along the SW side of the iron post.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°27.3' E., between sections 7 and 12.

- 40.262 The 1/4 section corner of sections 7 and 12, monumented with an iron post, 1 inch in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a steel fence post north and a scattered mound of stone, 2 ft. base, west of corner.

N. 0°26.2' E., beginning new measurement.

- 40.395 The corner of sections 1, 6, 7, and 12, monumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a scattered mound of stone west of corner.

Set a steel fence post alongside the iron post.

N. 0°23.3' E., between sections 1 and 6.

- 40.262 The 1/4 section corner of sections 1 and 6, monumented with an iron post, 1 inch in diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey; with a small mound of stone, west of corner.

Set a steel fence post alongside the iron post.

N. 0°26.0' E., beginning new measurement.

- 40.464 The corner of Townships 19 and 20 South, Ranges 7 and 8 West, monumented with an iron post, 3 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1940 resurvey.

Set a steel fence post alongside the iron post.

Dependent Resurvey of a Portion of the North Boundary,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Bausman in 1871 and the Resurvey Executed by
A. Nelson & E. Bird in 1941

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 1, 2, 35, and 36, on the north boundary of the township, monumented with an iron post, 2 inches in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 4 ft. base, 3 ft. high, west of corner,

from which the remaining 1934 bearing tree:

A cedar, 10 inches in diameter, bears N. 4° E., 41 links distance, marked S36 BT on open blaze.

Set a steel fence post alongside the iron post.

S. 89°57.2' W., between sections 2 and 35.

- 40.158 The 1/4 section corner of sections 2 and 35, monumented with an iron post, 1 inch in diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey; with a mound of stone, 4 ft. base, 2 ft. high, north of corner.

Set a steel fence post alongside the iron post.

S. 89°57.5' W., beginning new measurement.

- 40.123 The corner of sections 2, 3, 34, and 35, monumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, in a N and S barbed wire fence, with brass cap marked as described in the official record of the 1941 resurvey.

From the corner of sections 3, 4, 33, and 34, on the north boundary of the township, monumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey.

S. 89°42.9' W., between sections 4 and 33.

- 20.017 Point for the E 1/16 section corner for sections 4 and 33, not monumented.

- 40.034 The 1/4 section corner of sections 4 and 33, monumented with a decayed iron post, 1 inch in diameter, broken at ground surface, with the remaining iron post lying on ground alongside, 10 inches long, with a brass cap marked as described in the official record of the 1941 resurvey.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Drive a steel fence post 5 ft. long, 4 ft. 8 inches in the ground, set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, over the top of the fence post, with aluminum cap marked:

T 19 S
S 33
1/4 —————
S 4
T 20 S R 7 W
2008

Deposit the 1941 decayed iron post alongside the aluminum post.

Corner is located in a swamp.

From the corner of sections 4, 5, 32, and 33, on the north boundary of the township, monumented with an iron post, 2 inches in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey.

N. 89°57.4' W., between sections 5 and 32.

20.165 Point for the E 1/16 section corner of sections 5 and 32.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

T 19 S R 7 W
S 32
E 1/16 —————
S 5
T 20 S
2008

Corner is located 10 inches west of a N and S barbed wire fence.

40.330 The 1/4 section corner of sections 5 and 32, monumented with an iron post, 1 inch in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey.

Set a steel fence post alongside the iron post.

N. 89°57.9' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.300 The corner of sections 5, 6, 31, and 32, monumented with an iron post, 2 inches in diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey.

Set a steel fence post alongside the iron post.

S. $89^{\circ}52.7'$ W., between sections 6 and 31.

- 40.245 The 1/4 section corner of sections 6 and 31, monumented with an iron post, 1 inch in diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1941 resurvey.

Set a steel fence post alongside the iron post.

S. $89^{\circ}48.7'$ W., beginning new measurement.

- 40.274 The corner of Townships 19 and 20 South, Ranges 7 and 8 West, hereinbefore described.
-

Dependent Resurvey of a Portion of the Subdivisional Lines,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Bausman
in 1871 and the Resurvey Executed by
A. Nelson, et al. in 1934-36

From the corner of sections 11 and 12 only, monumented with an iron post, 2 inches in diameter, firmly set, in a collar of stone, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 5 ft. base, 2 ft. high, north of corner.

Set a steel fence post alongside the iron post.

N. $0^{\circ}04.5'$ W., between sections 11 and 12.

- 40.152 The 1/4 section corner of sections 11 and 12, monumented with an iron post, 1 inch in diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey.

Set a steel fence post alongside the iron post.

N. $0^{\circ}04.2'$ W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.150 The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 inches in diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 3 ft. base, 2 ft. high, west of corner.
-

N. 0°01.5' E., between sections 1 and 2.

- 40.498 The 1/4 section corner of sections 1 and 2, monumented with an iron post, 1 inch in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 4 ft. base, 3 ft. high, west of corner,

from which the remaining 1934 bearing tree:

A cedar, 14 inches in diameter, bears N. 7° W., 39.5 links distance, with scribe marks visible on open blaze.

Set a steel fence post alongside the iron post.

N. 0°00.4' E., beginning new measurement.

- 45.087 The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.
-

From the 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch in diameter, firmly set, in a mound of stone, 6 ft. base, with brass cap marked as described in the official record of the 1934-36 resurvey.

N. 0°41.6' E., between sections 14 and 15.

- 20.050 Point for the N 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

N 1/16
S 15 | S 14
2007

Set a steel fence post along the SW side of the aluminum post.

Corner is 6.8 links SE of a fence corner for barbed wire fences extending north and east.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.100 The corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 inches in diameter, firmly set, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 5 ft. base, 2 ft. high, west of corner.

From the corner of sections 11 and 12 only.

N. 89°07.4' W., on the south boundary of section 11.

- 2.373 The closing corner of sections 13 and 14, hereinafter described.

- 40.232 The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch in diameter, firmly set, in a mound of stone, 2 ft. base, with brass cap marked as described in the official record of the 1934-36 resurvey; with a steel fence post alongside.

N. 89°08.7' W., beginning new measurement.

- 20.109 Point for the W 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

	T 20 S R 7 W
	S 11
W 1/16	<hr/>
	S 14
	2008

Set a steel fence post alongside the aluminum post.

Corner is located in level saltgrass meadow. A N and S barbed wire fence bears west, 174 links distance.

- 40.218 The corner of sections 10, 11, 14, and 15.

Reestablishment of the Survey Executed by
A. Nelson, et al. in 1934-36

From the corner of sections 13 and 24 only, monumented with an iron post, 2 inches in diameter, firmly set, projecting 12 inches above a collar of stone, 3 ft. base, with brass cap marked as described in the official record of the 1934-36 survey,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

from which the 1934-36 bearing trees:

A juniper, 24 inches in diameter, bears N. $62^{\circ}15'$ E., 220 links distance, with scribe marks on a mostly healed blaze.

A juniper, 12 inches in diameter, bears S. $36^{\circ}45'$ E., 34 links distance, with scribe marks T20S R7W S24 BT.

N. $0^{\circ}00.6'$ W., along the west boundary of section 13.

1.669 The closing corner of sections 14 and 23, hereinafter described.

40.014 The $1/4$ section corner of section 13 only, monumented with an iron post, 1 inch in diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 1934-36 survey,

from which the 1934-36 bearing tree:

A juniper, 16 inches in diameter, bears S. 48° E., 18 links distance, with scribe marks on a partially healed blaze.

N. $0^{\circ}00.4'$ W., beginning new measurement.

0.774 The $1/4$ section corner of section 14 only, monumented with an iron post, 1 inch in diameter, firmly set, projecting 2 inches above a mound of stone, 2 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1934-36 survey,

from which the 1934-36 bearing tree:

A juniper, 18 inches in diameter, bears S. 62° W., 51 links distance, with scribe marks $1/4$ S14 BT. (Record: S. 59° W.)

40.787 The closing corner of sections 13 and 14, at intersection with the south boundary of section 11, monumented with an iron post, 2 inches in diameter, firmly set, in a mound of stone, 6 ft. base, with brass cap marked as described in the official record of the 1934-36 survey.

From the $1/4$ section corner of section 23 only, monumented with an iron post, 1 inch in diameter, in a mound of stone, 3 ft. base, 6 inches high, to top of brass cap marked as described in the official record of the 1934-36 survey.

S. $89^{\circ}41.6'$ E., along the south boundary of section 14.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 0.934** The 1/4 section corner of section 14 only, monumented with an iron post, 1 inch in diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1934-36 survey; with a mound of stone, 4 ft. base, 1 ft. high, 3 links north of corner.
-

S. 89°53.0 E., beginning new measurement.

- 39.058** The closing corner of sections 14 and 23, at intersection with the west boundary of section 13, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a collar of stone, 3 ft. base, with brass cap marked as described in the official record of the 1934-36 survey,

from which the 1934-36 bearing trees:

A juniper, 14 inches in diameter, bears S. 23° W., 258 links distance, with scribe marks T20S R7W S23 BT.

A juniper, 12 inches in diameter, bears N. 89° W., 100 links distance, with scribe marks T20S R7W S14 BT.

Reestablishment of the Survey Executed by
J. Bausman in 1871

From the corner of sections 10, 11, 14, and 15.

N. 0°02.0' E., between sections 10 and 11.

- 39.988** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set a steel fence post, 5 ft. long, 4 ft. in the ground, in 6 inch deep water, with a second steel fence post, 5 ft. long, 2 ft. in the ground, against the first steel fence post.

Corner is located in marsh and grasses, 150 links wide, bears S. 30° W. and N. 30° E.

- 79.976** Point for the corner of sections 2, 3, 10, and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W

S 3	S 2
S 10	S 11

2008

Set a steel fence post alongside the aluminum post.

Corner is located in marsh and approximately 1 chain south of a portion of Clear Lake shore line.

From the corner of sections 1, 2, 11, and 12.

N. 89°13.2' W., between sections 2 and 11.

40.298 The 1/4 section corner of sections 2 and 11, monumented with a lava stone 18 X 10 X 6 inches, dimly marked 1/4; in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 2
1/4 —————
S 11
2007

Deposit the marked stone, alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of corner.

Set a steel fence post alongside the aluminum post.

N. 89°30.7 W., beginning new measurement.

19.991 Point for the W 1/16 section corner of sections 2 and 11.

Cement a rebar, 8 inches long, 5/8 inches in diameter, drilled 4 inches into solid rock, with an aluminum cap marked:

T 20 S R 7 W
S 2
W 1/16 —————
S 11
2008

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, north of corner.

Set a steel fence post 6 links west of the corner.

39.982 The corner of sections 2, 3, 10, and 11.

N. $0^{\circ}29.5'$ W., between sections 2 and 3.

39.989 Point for the $1/4$ section corner of sections 2 and 3, determined at a fence corner with barbed wire fences extending N and E. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W	
$1/4$	
S 3	S 2
2008	

N. $0^{\circ}26.4'$ E., beginning new measurement.

44.648 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

Reestablishment of the Survey Executed by J. Bausman
in 1871 and the Resurvey Executed by
A. Nelson, et al. in 1934-36

From the $1/4$ section corner of section 28 only, monumented with an iron post, 1 inch in diameter, leaning and loosely set, in a scattered mound of stone, with brass cap marked as described in the official record of the 1934-36 resurvey.

At the corner point

Re-set the iron post, 36 inches long, 30 inches in the ground, in a mound of stone, 3 ft. base to top of brass cap.

Set a steel fence post along the south side of the iron post.

N. $0^{\circ}38.3'$ E., along the east boundary of section 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

39.433 The closing corner of sections 22 and 27, monumented with an iron post, 2 inches in diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 3 ft. base, 1 ft. high, east of corner.

40.336 The corner of sections 21 and 28 only, monumented with an iron post, 2 inches in diameter; firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 3 ft. base, 1 1/2 ft. high, 2 links west of corner.

N. 0°35.1' E., between sections 21 and 22.

40.360 The 1/4 section corner of sections 21 and 22, monumented with an iron post, 1 inch in diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 3 ft. base, 2 ft. high, west of corner.

N. 0°34.3' E., beginning new measurement.

40.371 The corner of sections 15, 16, 21, and 22, monumented with an iron post, 2 inches in diameter, firmly set, in a mound of stone, 6 ft. base to top of brass cap marked as described in the official record of the 1934-36 resurvey.

From the 1/4 section corner of sections 15 and 22, monumented with an iron post, 1 inch in diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a mound of stone, 4 ft. base, 2 ft. high, north of corner.

N. 89°51.3' W., between sections 15 and 22.

40.295 The corner of sections 15, 16, 21, and 22.

Reestablishment of the Survey Executed by
J. Bausman in 1871

N. 0°28.1' E., between sections 15 and 16.

40.019 The 1/4 section corner of sections 15 and 16, monumented with a lava stone, 10 X 8 X 5 inches, dimly marked 1/4, in a small mound of stone.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 16 | S 15
2007

Deposit the marked stone alongside the aluminum post.

N. 0°25.6' E., beginning new measurement.

20.592 Point for the N 1/16 section corner of sections 15 and 16, not monumented.

41.184 Point for the corner of sections 9, 10, 15, and 16, determined at a fence corner with barbed wire fences extending north and east, there is no remaining evidence of the original corner. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 9 | S 10
S 16 | S 15
2007

From the corner of sections 10, 11, 14, and 15.

N. 89°08.1' W., between sections 10 and 15.

40.119 The 1/4 section corner of sections 10 and 15, monumented with a decayed wood post, 4 inches in diameter, firmly set, projecting 12 inches above the ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 10
1/4 —————
S 15
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89°04.8' W., beginning new measurement.

20.406 Point for the W 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

	S 10
W 1/16	<hr/>
	S 15
	2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 3 links north and 3 links west of west fence post for a steel panel gate in an E and W barbed wire fence. The gate is across a N and S dirt road.

40.812 The corner of sections 9, 10, 15, and 16.

N. 0°40.3' E., between sections 9 and 10.

40.138 Point for the 1/4 section corner of sections 9 and 10, determined latitudinally by proportionate measurement and longitudinally by an old barbed wire fence line extending N and S.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W	
1/4	
S 9	S 10
2008	

Set a steel fence post alongside the aluminum post.

Corner is located in flat sand with grasses.

N. 0°22.2' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.137 Point for the corner of sections 3, 4, 9, and 10, determined latitudinally by proportionate measurement and longitudinally by an old barbed wire fence line extending N and S, falls in 3 ft. of water where it is unsuitable for monumentation; there is no remaining evidence of the original corner, not monumented.

From the corner of sections 2, 3, 10, and 11.

N. 88°53.3' W., between sections 3 and 10.

- 40.118 Point for the 1/4 section corner of sections 3 and 10, at proportionate distance, there is no remaining evidence of the original corner; falls in Clear Lake where it is unsuitable for monumentation, not monumented.

- 80.236 The point for the corner of sections 3, 4, 9, and 10.

N. 0°03.8' W., between sections 3 and 4.

- 40.136 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 4 | S 3
2008

Set a steel fence post alongside the aluminum post.

- 60.204 Point for the N 1/16 section corner of sections 3 and 4, not monumented.

- 82.981 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

Reestablishment of the Survey Executed by J. Bausman
in 1871 and the Resurvey Executed by
A. Nelson, et al. in 1934-36

From the standard corner of sections 32 and 33, monumented with an iron post, 2 inches in diameter, firmly set, projecting 18 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°24.1' E., between sections 32 and 33.

- 40.587 The 1/4 section corner of sections 32 and 33, monumented with an iron post, 1 inch in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey.

Set a steel fence post alongside the iron post.

N. 0°21.5' E., beginning new measurement.

- 40.506 The corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a 4 inch square cedar post along the north side of corner.

Before completion of this survey the iron post monument was bent over, the brass cap broken off, and the cedar post knocked out of the ground during rehabilitation of burnt area.

At the previously measured corner point, set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 29	S 28
S 32	S 33

2008

Deposit the cedar post, alongside the aluminum post

Set a steel fence post 1 link NE of the aluminum post.

From the 1/4 section corner of sections 28 and 33, monumented with an iron post, 1 inch in diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1934-36 resurvey; with a small mound of stone, north of corner.

Set a steel fence post alongside the iron post.

N. 89°47.8' W., between sections 28 and 33.

- 40.302 The corner of sections 28, 29, 32, and 33.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
J. Bausman in 1871

N. 0°38.7' E., between sections 28 and 29.

- 40.267 Point for the 1/4 section corner of sections 28 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 29 | S 28
2008

Set a steel fence post along the west side of the aluminum post.

- 80.534 Point for the corner of sections 20, 21, 28, and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 20 | S 21
S 29 | S 28
2008

Set a steel fence post along the east side of the aluminum post.

From the corner of sections 21 and 28 only.

N. 89°19.9' W., between sections 21 and 28.

- 40.302 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W
S 21
1/4 —————
S 28
2008

Set a steel fence post along the north side of the aluminum post.

80.604 The corner of sections 20, 21, 28, and 29.

N. 1°20.3' E., between sections 20 and 21.

40.275 Point for the 1/4 section corner of sections 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 20 | S 21
2008

Set a steel fence post along the east side of the aluminum post.

80.550 The corner of sections 16, 17, 20, and 21, monumented with an old cedar post, 40 inches long, 3 inches squared.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 17 | S 16
S 20 | S 21
2007

Deposit the cedar post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 15, 16, 21, and 22.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°27.9' W., between sections 16 and 21.

- 39.759 Point for the 1/4 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 16
1/4 —————
S 21
2008

Set a steel fence post along the west side of the aluminum post.

- 79.518 The corner of sections 16, 17, 20, and 21.
-

N. 1°57.0' W., between sections 16 and 17.

- 39.754 The 1/4 section corner of sections 16 and 17, monumented with an old cedar post, 40 inches long, 4 inches in diameter, squared on two sides.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 17 | S 16
2007

Deposit the cedar post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0°06.9' E., beginning new measurement.

- 40.224 The corner of sections 8, 9, 16, and 17, monumented with a cedar post, 40 inches long, 4 inches squared.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W

S 8	S 9
S 17	S 16

2007

Deposit the cedar post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 9, 10, 15, and 16.

S. 89°38.7' W., between sections 9 and 16.

40.703 Point for the 1/4 section corner of sections 9 and 16, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

	T 20 S R 7 W
	S 9
1/4	_____
	S 16
	2008

Set a steel fence post alongside the aluminum post.

81.406 The corner of sections 8, 9, 16, and 17.

N. 0°54.5' E., between sections 8 and 9.

40.283 The 1/4 section corner of sections 8 and 9, monumented with an old cedar post, 28 inches long, 3 inches squared.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

	T 20 S R 7 W
	1/4
S 8	S 9
	2007

Deposit the cedar post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

N. $1^{\circ}42.5'$ E., beginning new measurement.

- 40.403 The corner of sections 4, 5, 8, and 9, monumented with a decayed wood post, broken at ground surface.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 5	S 4
S 8	S 9

2007

Deposit the wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the point for the corner of sections 3, 4, 9, and 10.

S. $89^{\circ}55.2'$ W., between sections 4 and 9.

- 40.137 Point for the 1/4 section corner of sections 4 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 4

1/4

S 9

2008

Set a steel fence post alongside the aluminum post.

- 80.274 The corner of sections 4, 5, 8, and 9.
-

N. $0^{\circ}03.2'$ E., between sections 4 and 5.

- 40.089 The 1/4 section corner of sections 4 and 5, monumented with a decayed wood post, broken at ground surface.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 5 | S 4
2007

Deposit the wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0°06.2' E., beginning new measurement.

20.048 Point for the N 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

N 1/16
S 5 | S 4
2008

Set a steel fence post alongside the aluminum post.

42.601 The corner of sections 4, 5, 32, and 33, on the north boundary of the Township, hereinbefore described.

From the standard corner of sections 31 and 32, monumented with an iron post, 2 inches in diameter, firmly set, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1937 resurvey.

N. 0°40.5' E., between sections 31 and 32.

39.362 Point for the 1/4 section corner of sections 31 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 31 | S 32
2008

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

- 78.724 The corner of sections 29, 30, 31, and 32, monumented with an old cedar post, 36 inches long, 3 inches squared.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 30	S 29
S 31	S 32

2007

Deposit the cedar post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 28, 29, 32, and 33.

S. 88°39.1' W., between sections 29 and 32.

- 40.054 Point for the 1/4 section corner of sections 29 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 29

1/4

S 32
2008

Set a steel fence post alongside the aluminum post.

- 80.108 The corner of sections 29, 30, 31, and 32.
-

N. 88°15.1' W., between sections 30 and 31.

- 40.446 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W
S 30
1/4 —————
S 31
2008

Set a steel fence post alongside the aluminum post.

- 81.094** The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.
-

From the corner of sections 29, 30, 31, and 32.

N. 0°16.8' E., between sections 29 and 30.

- 40.700** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 30 | S 29
2008

Set a steel fence post along the west side of the aluminum post.

Corner is located on a sand dune.

- 81.400** Point for the corner of sections 19, 20, 29, and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 19 | S 20
S 30 | S 29
2008

Set a steel fence post along the east side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 20, 21, 28, and 29.

S. $89^{\circ}16.7'$ W., between sections 20 and 29.

- 40.293 Point for the 1/4 section corner of sections 20 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 20
1/4 —————
S 29
2008

Set a steel fence post 1 link west of the corner.

- 80.586 The corner of sections 19, 20, 29, and 30.
-

N. $88^{\circ}48.5'$ W., between sections 19 and 30.

- 40.308 Point for the 1/4 section corner of sections 19 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 19
1/4 —————
S 30
2008

Set a steel fence post 1 link west of the aluminum post.

- 80.747 The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.
-

From the corner of sections 19, 20, 29, and 30.

N. $1^{\circ}07.9'$ E., between sections 19 and 20.

- 40.707 Point for the 1/4 section corner of sections 19 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W

1/4

S 19 | S 20

2008

Set a steel fence post along the north side of the aluminum post.

- 81.414 Point for the corner of sections 17, 18, 19, and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 18	S 17
S 19	S 20

2008

Set a steel fence post along the east side of the aluminum post.

From the corner of sections 16, 17, 20, and 21.

S. 89°53.9' W., between sections 17 and 20.

- 40.418 Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

S 17

1/4

S 20

2008

Set a steel fence post along the west side of the aluminum post.

- 80.836 The corner of sections 17, 18, 19, and 20.

N. 88°46.4' W., between sections 18 and 19.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.428 The 1/4 section corner of sections 18 and 19, monumented with an old cedar post, 34 inches long, 3 inches in diameter, squared on one side.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 18
1/4 —————
S 19
2007

Deposit the cedar post alongside the aluminum post.

Deposit a steel fence post alongside the aluminum post.

N. 89°43.6' W., beginning new measurement.

- 41.188 The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.
-

From the corner of sections 17, 18, 19, and 20.

N. 0°02.2' W., between sections 17 and 18.

- 40.699 Point for the 1/4 section corner of sections 17 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 18 | S 17
2008

Set a steel fence post alongside the aluminum post.

- 81.398 The corner of sections 7, 8, 17, and 18, monumented with a decayed wood post, broken at ground surface.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W

S 7	S 8
S 18	S 17

2007

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 8, 9, 16, and 17.

N. 89°05.4' W., between sections 8 and 17.

39.870 The 1/4 section corner of sections 8 and 17, monumented with a lava stone 15 X 10 X 4 inches, firmly set, dimly marked 1/4; with a cedar post, 36 inches long, 4 inches squared, alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

	T 20 S R 7 W
	S 8
1/4	_____
	S 17
	2007

Deposit the marked stone and cedar post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89°02.3' W., beginning new measurement.

39.742 The corner of sections 7, 8, 17, and 18.

N. 89°41.2' W., between sections 7 and 18.

40.387 The 1/4 section corner of sections 7 and 18, monumented with a decayed wood post, 36 inches long.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W
S 7
1/4 —————
S 18
2008

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post along the south side of the aluminum post.

N. 89°35.4' W., beginning new measurement.

40.478 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°12.1' E., between sections 7 and 8.

40.378 Point for the 1/4 section corner of sections 7 and 8, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 7 | S 8
2008

Set a steel fence post along the SW side of the aluminum post.

80.756 The corner of sections 5, 6, 7, and 8, monumented with a decayed wood post, 33 inches long, 4 inches in diameter, projecting 6 inches above the ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 6 | S 5
S 7 | S 8
2008

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 4, 5, 8, and 9.

N. 89°13.7' W., between sections 5 and 8.

41.164 The 1/4 section corner of sections 5 and 8, monumented with a decayed wood post, 15 inches long, squared, broken at ground surface.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 5
1/4 —————
S 8
2008

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

N. 88°47.9' W., beginning new measurement.

39.992 The corner of sections 5, 6, 7, and 8.

N. 89°41.1' W., between sections 6 and 7.

40.341 The 1/4 section corner of sections 6 and 7, monumented with a decayed wood post, set 21 inches in the ground, broken at ground surface, with the remaining post, 17 inches long, lying alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
S 6
1/4 —————
S 7
2008

Deposit the decayed wood post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post along the south side of the aluminum post.

N. $89^{\circ}43.9'$ W., beginning new measurement.

40.164 The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

From the corner of sections 5, 6, 7, and 8.

N. $0^{\circ}35.8'$ E., between sections 5 and 6.

39.987 The $1/4$ section corner of sections 5 and 6, monumented with a decayed wood post, 10 inches long, broken at ground surface.

At the corner point

Set an aluminum post, 30 inches long, $2\frac{1}{2}$ inches in diameter, 24 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
1/4
S 6 | S 5
2008

Deposit the decayed wood post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. $0^{\circ}16.1'$ E., beginning new measurement.

41.367 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

The Subdivision of Section 4,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the $1/4$ section corner of sections 4 and 9.

N. $0^{\circ}00.1'$ E., on the N-S center line of section 4.

40.115 Point for the center $1/4$ section corner of section 4 at the intersection with the E-W center line of section.

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

C 1/4 S 4

2008

Set a steel fence post alongside the aluminum post.

60.173 Point for the center N 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

C
|
N 1/16 | S 4
|
C
2008

Set a steel fence post alongside the aluminum post.

82.838 The 1/4 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 3 and 4.

S. 89°53.2' W., on the E-W center line of section 4.

20.043 Point for the center E 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

E 1/16
C ————— C
S 4
2008

Set a steel fence post alongside the aluminum post.

A fence corner for barbed wire fences extending N and E bears S. 24°15' E., 86.1 links distance.

40.086 The center 1/4 section corner of section 4.

80.183 The 1/4 section corner of sections 4 and 5.

From the center E 1/16 section corner of section 4.

THE SUBDIVISION OF SECTION 4,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°01.9' W., on the N-S center line of the NE 1/4 of section 4.

20.063 Point for the NE 1/16 section corner of section 4, at intersection with the E-W centerline of the NE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

NE 1/16 S 4

2008

Set a steel fence post alongside the aluminum post.

42.784 The point for the E 1/16 section corner of section 4 and 33, on the north boundary of the township, hereinbefore described.

From the point for the N 1/16 section corner of sections 3 and 4.

S. 89°52.5' W., on the E-W center line of the NE 1/4 of section 4.

20.031 The NE 1/16 section corner of section 4.

40.062 The center N 1/16 section corner of section 4.

From the center N 1/16 section corner of section 4.

S. 89°52.2' W., on the E-W center line of the NW 1/4 of section 4.

40.060 The N 1/16 section corner of sections 4 and 5.

The Subdivision of Section 5,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 8.

N. 0°39.2' E., on the N-S center line of section 5.

40.190 Point for the center 1/4 section corner of section 5 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 20 S R 7 W

C 1/4 S 5

2008

Set a steel fence post alongside the aluminum post.

60.282 Point for the center N 1/16 section corner of section 5, not monumented.

82.172 The 1/4 section corner of sections 5 and 32, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 4 and 5.

N. 89°05.1' W., on the E-W center line of section 5.

20.370 Point for the center E 1/16 section corner of section 5, not monumented.

40.740 The center 1/4 section corner of section 5.

80.764 The 1/4 section corner of sections 5 and 6.

From the point for the center E 1/16 section corner of section 5.

N. 0°22.5' E., on the N-S center line of the NE 1/4 of section 5.

20.070 Point for the NE 1/16 section corner of section 5, at intersection with the E-W center line of the NE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

NE 1/16 S 5

2008

42.291 The E 1/16 section corner of sections 5 and 32, on the north boundary of the township, hereinbefore described.

From the N 1/16 section corner of sections 4 and 5.

N. 89°01.2' W., on the E-W center line of the NE 1/4 of section 5.

THE SUBDIVISION OF SECTION 5,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 20.273 The NE 1/16 section corner of section 5.
40.546 The point for the center N 1/16 section corner of section 5.
-

The Subdivision of Section 10,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0°01.9' E., on the N-S center line of section 10.

- 40.087 Point for the center 1/4 section corner of section 10 at the intersection with the E-W center line of section, not monumented.
80.149 The point for the 1/4 section corner of sections 3 and 10.
-

From the 1/4 section corner of sections 10 and 11.

N. 88°59.8' W., on the E-W center line of section 10.

- 40.119 The point for the center 1/4 section corner of section 10.
60.298 Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W
W 1/16
C ————— C
S 10
2008

Set a steel fence post alongside the aluminum post.

Corner is located in sand dunes and grasses, on the southwesterly end of Clear Lake.

- 80.477 The 1/4 section corner of sections 9 and 10.
-

From the W 1/16 section corner of sections 10 and 15.

N. 0°21.1' E., on the N-S center line of the SW 1/4 of section 10.

- 40.112 The center W 1/16 section corner of section 10.

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 11,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 11 and 14.

N. 0°07.5' W., on the N-S center line of section 11.

- 40.066 Point for the center 1/4 section corner of section 11 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

C 1/4
S 11

2008

Set a steel fence post alongside the aluminum post. Corner is located on level land of grasses, sage and greasewood.

- 80.236 The 1/4 section corner of sections 2 and 11.
-

From the 1/4 section corner of sections 11 and 12.

N. 89°14.8' W., on the E-W center line of section 11.

- 40.263 The center 1/4 section corner of section 11.

- 60.313 Point for the center W 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

W 1/16

C ————— C

S 11

2008

Set a steel fence post alongside the aluminum post.

Corner is located on a level salt grass meadow. A N and S barbed wire fence bears west, 115 links distance.

- 80.363 The 1/4 section corner of sections 10 and 11.
-

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the W 1/16 section corner of sections 11 and 14.

N. 0°02.8' W., on the N-S center line of the SW 1/4 of section 11.

40.027 The center W 1/16 section corner of section 11.

From the center W 1/16 section corner of section 11.

N. 0°02.8' W., on the N-S center line of the NW 1/4 of section 11.

40.079 The W 1/16 section corner of sections 2 and 11.

The Subdivision of Section 14,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the 1/4 section corner of section 14 only.

N. 0°51.1' E., on the N-S center line of section 14.

39.581 Point for the center 1/4 section corner of section 14 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

C 1/4

S 14

2008

Set a steel fence post alongside the aluminum post.

Corner is located in rolling sand dunes with grasses and sage brush.

59.610 Point for the center N 1/16 section corner of section 14, not monumented.

79.639 The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of section 14 only.

N. 89°12.2' W., on the E-W center line of section 14.

38.463 The center 1/4 section corner of section 14.

THE SUBDIVISION OF SECTION 14,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

58.518 Point for the center W 1/16 section corner of section 14, not monumented.

78.573 The 1/4 section corner of sections 14 and 15.

From the point for the center W 1/16 section corner of section 14.

N. 0°46.3' E., on the N-S center line of the NW 1/4 of section 14.

20.039 Point for the NW 1/16 section corner of section 14, at intersection with the E-W center line of the NW 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

NW 1/16
S 14

2008

Set a steel fence post alongside the aluminum post.

Corner is located on a level salt grass meadow. The corner of barbed wire fences extending north, south, and west, bears S.87°20' W., 174 links distance.

40.078 The W 1/16 section corner of sections 11 and 14.

From the point for the center N 1/16 section corner of section 14.

N. 89°10.5' W., on the E-W center line of the NW 1/4 of section 14.

20.082 The NW 1/16 section corner of section 14.

40.164 The N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 15,
Township 20 South, Range 7 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0°49.2' E., on the N-S center line of section 15.

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.038 Point for the center 1/4 section corner of section 15 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 20 S R 7 W

C 1/4 S 15

2007

Set a steel fence post along the north side of the aluminum post.

- 60.347 Point for the center N 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 12 inches in the ground to solid rock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

C
|
N 1/16 | S 15
|
C
2007

Set a steel fence post 1 link north of the aluminum post.

- 80.656 The 1/4 section corner of sections 10 and 15.
-

From the 1/4 section corner of sections 14 and 15.

N. 89°52.5' W., on the E-W center line of section 15.

- 40.215 The center 1/4 section corner of section 15.

- 60.483 Point for the center W 1/16 section corner of section 15, not monumented.

- 80.751 The 1/4 section corner of sections 15 and 16.
-

From the N 1/16 section corner of sections 14 and 15.

N. 89°30.2' W., on the E-W center line of the NE 1/4 of section 15.

- 40.166 The center N 1/16 section corner of section 15.
-

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 20 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the center W 1/16 section corner of section 15.

N. 0°37.3' E., on the N-S center line of the NW 1/4 of section 15.

20.450 Point for the NW 1/16 section corner of section 15, at intersection with the E-W center line of the NW 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

NW 1/16 S 15

2007

Set a steel fence post along the north side of the aluminum post.

40.900 The W 1/16 section corner of sections 10 and 15.

From the center N 1/16 section corner of section 15.

N. 89°28.7' W., on the E-W center line of the NW 1/4 of section 15.

20.336 The NW 1/16 section corner of section 15.

40.672 The point for the N 1/16 section corner of sections 15 and 16.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Daniel Webb	Chief Cadastral Surveyor
Steve Hope	Cadastral Surveyor
Calvert C. Norton	Survey Technician
Adrian Kurip	Survey Technician

CERTIFICATE OF SURVEY

We, **Daniel T. Gillins, Cadastral Surveyor**, under the supervision of **Ronald K. Baugh, Supervisory Cadastral Surveyor**, hereby certify upon honor, that in pursuance of Special Instructions bearing the date of the **31st day of August, 2007**, we have executed a **dependent resurvey of the west boundary, a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 4, 5, 10, 11, 14, and 15, in Township 20 South, Range 7 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 28, 2009

Date

Ronald K. Baugh
Supervisory Cadastral Surveyor

April 28, 2009

Date

Daniel T. Gillins
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of the west boundary, a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 4, 5, 10, 11, 14, and 15, in Township 20 South, Range 7 West, Salt Lake Meridian, Utah,**

executed by **Daniel T. Gillins, Cadastral Surveyor**, under the supervision of **Ronald K. Baugh, Supervisory Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

July 6, 2009

Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)